

Walraven BISOFIX® PIR60 + HD500

(D0394)

for insulated pipes



Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with HD500 clamp
- HD500 clamp with M8/M10 and M10/M12 connection nut
- fire class B2
- PIR density for $D < 110\text{mm} = 80\text{kg/m}^3$
- PIR density for $D > 110\text{mm} = 120\text{kg/m}^3$
- thermal conductivity lambda (approx. value): 0.30 W/(mK)
- product is part of the Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range $-45\text{ °C} - +105\text{ °C}$

Product Number	VVS Number	Connection Thread	Total Height	Total Width	Total Length	Insulation Thickness	Maximum Allowed Load Faz
Reference letter		G	H	W	L	Is	Fa,z
Unit description			mm	mm	mm	mm	N
I603306108	018002690	M16	263	299	75	60	800
I603306114	018002691	M16	277	322	75	60	1,790
I603306133	018002693	M16	290	335	100	60	2,190
I603306140	018002694	M16	300	345	100	60	2,280
I603306159	018002696	M16	315	360	100	60	2,450
I603306168	018002697	M16	324	367	100	60	2,620