


Walraven WDI2R Drop-in Anchor

(L0321)

reduced length drop-in anchor with a lip collar



Features & benefits

- European Technical Assessment according to EAD 330747-00-0601 (May 2018) for fasteners for use in concrete for redundant non-structural systems.
- increased productivity – the reduced 25mm anchor length minimizes drilling depth and speeds up installation
- approved applications in precast prestressed hollow core slabs
- fire resistance class R30-R120 for design of anchorages under exposure to fire
- complies with VdS CEA 4001: 2024-01 (08) for applications with sprinkler systems in concrete elements
- substrate type: cracked concrete, non-cracked concrete
- for loads and more information, refer to the product data sheet and/or the ETA report
- material: steel
- zinc plated

Product Number	Thread Size	Thread Type	Total Height	Total Width	Total Length	Drill Hole Diameter	Min. Drill Hole Depth	Standard Embedment Depth	Minimum Substrate Thickness
Reference Letter	TS	TT	H	W	L	d0	h0 min	hnom	hmin
Unit description			mm	mm	mm	mm	mm	mm	mm
6103310825	M8	Metric	11	11	25	10	28	≥ 25	80
6103311025	M10	Metric	13	13	25	12	28	≥ 25	80
6103311225	M12	Metric	16	16	25	15	29	≥ 25	80