

Walraven BISOFIX® E13 + Bifix® G2

(D0306)

for insulated pipes



Features & benefits

- for combination with elastomeric foam insulation
- vapourproof glueable with pipe insulation
- insulating pipe support with Bifix® G2 clamp
- Bifix® G2 with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for D <80mm = 80kg/m³
- PIR density for D >80mm = 120kg/m³
- product is part of the Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range -45 °C - +105 °C

| Product Number | Connection Thread | Total Height | Total Width | Total Length | Insulation Thickness | Maximum Allowed Load Faz |
|------------------|-------------------|--------------|-------------|--------------|----------------------|--------------------------|
| Reference letter | G | H | W | L | Is | F _{0,z} |
| Unit description | | mm | mm | mm | mm | N |
| I133008008 | M8/M10 | 62 | 80 | 50 | 13.3 | 100 |
| I133008010 | M8/M10 | 62 | 80 | 50 | 13.3 | 100 |
| I133008012 | M8/M10 | 62 | 80 | 50 | 13.3 | 100 |
| I133008015 | M8/M10 | 66 | 84 | 50 | 13.3 | 100 |
| I133008018 | M8/M10 | 66 | 84 | 50 | 13.3 | 100 |
| I133008022 | M8/M10 | 73 | 91 | 50 | 13.5 | 100 |
| I133008028 | M8/M10 | 79 | 97 | 50 | 13.3 | 100 |
| I133008035 | M8/M10 | 86 | 104 | 50 | 13.3 | 100 |
| I133008042 | M8/M10 | 92 | 110 | 50 | 13.3 | 150 |
| I133008048 | M8/M10 | 100 | 118 | 50 | 13.3 | 225 |
| I133008054 | M8/M10 | 107 | 125 | 50 | 13.3 | 225 |
| I133008057 | M8/M10 | 107 | 125 | 50 | 13.3 | 350 |
| I133008060 | M8/M10 | 115 | 134 | 50 | 13.9 | 350 |
| I133008064 | M8/M10 | 129 | 148 | 50 | 18 | 350 |
| I133008070 | M8/M10 | 129 | 148 | 50 | 16.3 | 425 |
| I133008076 | M8/M10 | 137 | 155 | 50 | 16.3 | 575 |
| I133008089 | M8/M10 | 154 | 172 | 50 | 17.9 | 875 |
| I133008102 | M8/M10 | 162 | 181 | 50 | 16.3 | 1,000 |
| I133008108 | M8/M10 | 162 | 181 | 50 | 16.3 | 1,075 |
| I133008114 | M8/M10 | 183 | 201 | 50 | 18.9 | 1,250 |
| I133008133 | M8/M10 | 195 | 217 | 100 | 16.3 | 1,475 |
| I133008140 | M8/M10 | 208 | 229 | 100 | 18.2 | 1,700 |
| I133008160 | M8/M10 | 227 | 248 | 100 | 16.3 | 1,950 |
| I133008168 | M8/M10 | 227 | 248 | 100 | 16.3 | 2,125 |