

Walraven BISOFIX® E19 + Bifix® G2

(D0318)

for insulated pipes



Features & benefits

- for combination with elastomeric foam insulation
- vapourproof glueable with pipe insulation
- insulating pipe support with Bifix® G2 clamp
- Bifix® G2 with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for D <80mm = 80kg/m³
- PIR density for D >80mm = 120kg/m³
- product is part of the Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range -45 °C - +105 °C

Product Number	Connection Thread	Total Height	Total Width	Total Length	Insulation Thickness	Maximum Allowed Load Faz
Reference letter	G	H	W	L	Is	F _{0,z}
Unit description		mm	mm	mm	mm	N
I193008012	M8/M10	73	91	50	19.3	100
I193008015	M8/M10	79	97	50	19.5	100
I193008018	M8/M10	79	97	50	19.3	100
I193008022	M8/M10	86	104	50	19.3	100
I193008028	M8/M10	92	110	50	19.3	100
I193008035	M8/M10	100	118	50	19.3	100
I193008042	M8/M10	107	125	50	19.3	150
I193008048	M8/M10	115	134	50	19.3	225
I193008054	M8/M10	129	148	50	23	225
I193008057	M8/M10	129	148	50	23	225
I193008060	M8/M10	129	148	50	19.9	350
I193008064	M8/M10	137	155	50	25.3	350
I193008070	M8/M10	154	172	50	27.3	452
I193008076	M8/M10	154	172	50	25.3	575
I193008089	M8/M10	162	181	50	25.3	875
I193008102	M8/M10	183	201	50	25.3	1,000
I193008108	M8/M10	183	201	50	25.3	1,075
I193008114	M8/M10	195	217	50	25.3	1,250
I193008133	M8/M10	227	248	100	26.2	1,475
I193008140	M8/M10	227	248	100	25.3	1,700
I193008160	M8/M10	239	261	100	25.3	1,950
I193008168	M8/M10	253	275	100	25.3	2,125
I193008010	M8/M10	73	91	50	19.3	100