

Walraven BISOFIX® E19 + HD500

(D0320)

for insulated pipes



Features & benefits

- for combination with elastomeric foam insulation
- vapourproof glueable with pipe insulation
- insulating pipe support with HD500 clamp
- HD500 clamp with M8/M10 and M10/M12 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 80\text{mm} = 80\text{kg/m}^3$
- PIR density for $D > 80\text{mm} = 120\text{kg/m}^3$
- product is part of the Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range $-45\text{ °C} - +105\text{ °C}$

Product Number	Outside Pipe Diameter	Connection Thread	Total Height	Total Width	Total Length	Insulation Thickness	Maximum Allowed Load
Reference Letter	D	G	H	W	L	Is	Fa,z
Unit description	mm		mm	mm	mm	mm	N
I193304076	76.1	M10/M12	170	193	50	25.3	575
I193304089	88.9	M10/M12	177	200	50	25.3	875
I193304102	101.6	M10/M12	191	215	50	25.3	1,000
I193304108	108	M10/M12	207	240	50	25.3	1,075
I193304114	114.3	M10/M12	207	240	50	25.3	1,250
I193304133	133	M10/M12	240	274	100	26.2	1,475
I193304140	139.7	M10/M12	240	274	100	25.3	1,700
I193304160	159 - 160	M10/M12	256	290	100	25.3	1,950
I193304168	168.3	M10/M12	256	290	100	25.3	2,125
I193304219	219.1	M16	315	360	100	25.3	3,525
I193304273	273.1	M16	358	403	100	25.3	3,525