

Walraven BISOFIX® E32 + Bifix® G2

(D0342)

for insulated pipes



Features & benefits

- for combination with elastomeric foam insulation
- vapourproof glueable with pipe insulation
- insulating pipe support with Bifix® G2 clamp
- Bifix® G2 with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 80\text{mm} = 80\text{kg/m}^3$
- PIR density for $D > 80\text{mm} = 120\text{kg/m}^3$
- product is part of the Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range $-45\text{ °C} - +105\text{ °C}$

Productnumber	Outside Pipe Diameter	Connection Thread	Total Height	Total Width	Total Length	Insulation Thickness	Maximum Allowed Load Faz
Reference Letter	D	G	H	W	L	Is	Fa,z
Unit description	mm		mm	mm	mm	mm	N
I323008012	12	M8/M10	100	118	50	32.3	100
I323008015	15	M8/M10	107	125	50	32.5	100
I323008018	17.2 - 18	M8/M10	107	125	50	32.3	100
I323008022	21.3 - 22	M8/M10	115	134	50	33	100
I323008028	27 - 28	M8/M10	129	148	50	36	100
I323008035	33.7 - 35	M8/M10	129	148	50	32.5	100
I323008042	42.4	M8/M10	137	155	50	32.8	150
I323008048	48.3	M8/M10	137	155	50	32.3	225
I323008054	54	M8/M10	154	172	50	35.3	225
I323008060	60.3	M8/M10	154	172	50	32.3	350
I323008064	64	M8/M10	183	201	50	44	350