


Walraven BISOFIX® PIR20 + 2S

(D0352)

for insulated pipes



Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with 2S clamp
- 2S clamp with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 110\text{mm}$ = 80kg/m^3
- PIR density for $D > 110\text{mm}$ = 120kg/m^3
- thermal conductivity λ (approx. value): 0.30 W/(mK)
- clamp: zinc plated
- temperature range $-45\text{ °C} - +105\text{ °C}$

Productnumber	Outside Pipe Diameter	Connection Thread	Total Height	Total Width	Total Length	Insulation Thickness	Maximum Allowed Load Faz
Reference Letter	D	G	H	W	L	Is	Fa,z
Unit description	mm		mm	mm	mm	mm	N
I203303015	15 - 16	M8/M10	83	93	75	20	160
I203303018	17.2 - 18	M8/M10	83	93	75	20	170
I203303022	21.3 - 22	M8/M10	83	93	75	20	180
I203303028	26.9 - 28	M8/M10	89	99	75	20	200
I203303034	33.7 - 35	M8/M10	96	111	75	20	220
I203303042	42.4	M8/M10	109	124	75	20	280
I203303054	54	M8/M10	119	136	75	20	320
I203303025	25	M8/M10	89	99	75	20	190
I203303032	32	M8/M10	96	111	75	20	210
I203303048	48.3	M8/M10	119	136	75	20	300
I203303076	76.1	M8/M10	136	153	75	20	390
I203303089	88.9	M8/M10	161	178	75	20	430
I203303114	114.3	M8/M10	186	203	100	20	1,110
I203303168	168.3	M8/M10	243	260	100	20	1,570