


Walraven BISOFIX® PIR30 + 2S

(D0362)

for insulated pipes



Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with 2S clamp
- 2S clamp with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 110\text{mm}$ = 80kg/m^3
- PIR density for $D > 110\text{mm}$ = 120kg/m^3
- thermal conductivity λ (approx. value): 0.30 W/(mK)
- clamp: zinc plated
- temperature range $-45\text{ }^\circ\text{C}$ - $+105\text{ }^\circ\text{C}$

Productnumber	Outside Pipe Diameter	Connection Thread	Total Height	Total Width	Total Length	Insulation Thickness	Maximum Allowed Load Faz
Reference Letter	D	G	H	W	L	Is	Fa,z
Unit description	mm		mm	mm	mm	mm	N
I303303018	17.2 - 18	M8/M10	103	118	75	30	190
I303303022	21.3 - 22	M8/M10	109	124	75	30	230
I303303028	26.9 - 28	M8/M10	119	136	75	30	300
I303303034	33.7 - 35	M8/M10	119	136	75	30	320
I303303042	42.4	M8/M10	127	143	75	30	350
I303303054	54	M8/M10	136	153	75	30	380
I303303015	15 - 16	M8/M10	103	118	75	30	170
I303303140	139.7	M8/M10	232	249	100	30	1,570
I303303048	48.3	M8/M10	136	153	75	30	370