

Walraven BISOFIX® PIR30 (40mm) + 2S

(D0363)

for insulated pipes



Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with 2S clamp
- 2S clamp with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 110\text{mm} = 80\text{kg/m}^3$
- PIR density for $D > 110\text{mm} = 120\text{kg/m}^3$
- thermal conductivity lambda (approx. value): 0.30 W/(mK)
- zinc plated
- temperature range $-45\text{ °C} - +105\text{ °C}$

Product Number	Connection Thread	Total Height	Total Width	Total Length	Insulation Thickness	Maximum Allowed Load Faz
Reference letter	G	H	W	L	Is	F _{0,z}
Unit description		mm	mm	mm	mm	N
I343303022	M8/M10	109	124	40	40	230
I343303028	M8/M10	119	136	40	40	300
I343303034	M8/M10	119	136	40	40	320
I343303042	M8/M10	127	143	40	40	350
I343303048	M8/M10	136	153	40	40	370
I343303054	M8/M10	136	153	40	40	380
I343303060	M8/M10	151	168	40	40	410
I343303064	M8/M10	151	168	40	40	420
I343303076	M8/M10	161	178	40	40	460
I343303089	M8/M10	177	194	40	40	500
I343303114	M8/M10	210	227	40	40	1,370