


Walraven BISOFIX® PIR40 + 2S

(D0372)

for insulated pipes



Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with 2S clamp
- 2S clamp with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 110\text{mm}$ = 80kg/m^3
- PIR density for $D > 110\text{mm}$ = 120kg/m^3
- thermal conductivity λ (approx. value): 0.30 W/(mK)
- clamp: zinc plated
- temperature range $-45\text{ °C} - +105\text{ °C}$

Productnumber	Outside Pipe Diameter	Connection Thread	Total Height	Total Width	Total Length	Insulation Thickness	Maximum Allowed Load Faz
Reference Letter	D	G	H	W	L	Is	Fa,z
Unit description	mm		mm	mm	mm	mm	N
I403303140	139.7	M8/M10	253	271	100	40	1,730
I403303034	33.7 - 35	M8/M10	136	153	75	40	370
I403303042	42.4	M8/M10	151	168	75	40	410
I403303054	54	M8/M10	161	178	75	40	440
I403303076	76.1	M8/M10	186	203	75	40	530
I403303108	108	M8/M10	221	239	100	40	690
I403303114	114.3	M8/M10	221	239	100	40	1,560
I403303018	17.2 - 18	M8/M10	127	143	75	40	340
I403303022	21.3 - 22	M8/M10	127	143	75	40	350
I403303028	26.9 - 28	M8/M10	136	153	75	40	350
I403303048	48.3	M8/M10	161	178	75	40	430