

## Walraven BISOFIX® PIR40 + 2S

(D0372)

for insulated pipes



### Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with 2S clamp
- 2S clamp with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for  $D < 110\text{mm} = 80\text{kg/m}^3$
- PIR density for  $D > 110\text{mm} = 120\text{kg/m}^3$
- thermal conductivity lambda (approx. value):  $0.30\text{ W/(mK)}$
- clamp: zinc plated
- temperature range  $-45\text{ °C} - +105\text{ °C}$

Product Number	Connection Thread	Total Height	Total Width	Total Length	Insulation Thickness	Maximum Allowed Load Faz
Reference letter	G	H	W	L	Is	F <sub>0,z</sub>
Unit description		mm	mm	mm	mm	N
I403303140	M8/M10	253	271	100	40	1,730
I403303012	M8/M10	119	136	75	40	300
I403303015	M8/M10	119	136	75	40	320
I403303018	M8/M10	127	143	75	40	340
I403303020	M8/M10	127	143	75	40	340
I403303022	M8/M10	127	143	75	40	350
I403303025	M8/M10	136	153	75	40	350
I403303028	M8/M10	136	153	75	40	350
I403303032	M8/M10	136	153	75	40	370
I403303034	M8/M10	136	153	75	40	370
I403303040	M8/M10	151	168	75	40	400
I403303042	M8/M10	151	168	75	40	410
I403303048	M8/M10	161	178	75	40	430
I403303054	M8/M10	161	178	75	40	440
I403303057	M8/M10	161	178	75	40	460
I403303060	M8/M10	168	185	75	40	470
I403303064	M8/M10	168	185	75	40	490
I403303070	M8/M10	177	194	75	40	510
I403303076	M8/M10	186	203	75	40	530
I403303089	M8/M10	199	217	75	40	620
I403303102	M8/M10	210	227	100	40	650
I403303108	M8/M10	221	239	100	40	690
I403303114	M8/M10	221	239	100	40	1,560
I403303133	M8/M10	243	260	100	40	1,670