

## Walraven BISOFIX® PIR40 + Bifix® G2

(D0374)

for insulated pipes



### Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with Bifix® G2 clamp
- Bifix® G2 with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for  $D < 110\text{mm} = 80\text{kg/m}^3$
- PIR density for  $D > 110\text{mm} = 120\text{kg/m}^3$
- thermal conductivity lambda (approx. value):  $0.30\text{ W/(mK)}$
- product is part of the Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range  $-45\text{ °C} - +105\text{ °C}$

Product Number	Connection Thread	Total Height	Total Width	Total Length	Insulation Thickness	Maximum Allowed Load Faz
<i>Reference letter</i>	<i>G</i>	<i>H</i>	<i>W</i>	<i>L</i>	<i>Is</i>	<i>Fa,z</i>
<i>Unit description</i>		<i>mm</i>	<i>mm</i>	<i>mm</i>	<i>mm</i>	<i>N</i>
1403008048	M8/M10	154	172	75	40	430