


Walraven BISOFIX® PIR50 + 2S

(D0382)

for insulated pipes



Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with 2S clamp
- 2S clamp with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 110\text{mm}$ = 80kg/m^3
- PIR density for $D > 110\text{mm}$ = 120kg/m^3
- thermal conductivity lambda (approx. value): 0.30 W/(mK)
- clamp: zinc plated
- temperature range $-45\text{ °C} - +105\text{ °C}$

Productnumber	Outside Pipe Diameter	Connection Thread	Total Height	Total Width	Total Length	Insulation Thickness	Maximum Allowed Load Faz
Reference Letter	D	G	H	W	L	Is	Fa,z
Unit description	mm		mm	mm	mm	mm	N
I503303060	60.3	M8/M10	186	203	75	50	540
I503303076	76.1	M8/M10	210	227	75	50	650
I503303089	88.9	M8/M10	221	239	75	50	690
I503303114	114.3	M8/M10	243	260	100	50	1,680
I503303028	26.9 - 28	M8/M10	161	178	75	50	350