

Walraven BISOFIX® PIR60 + 2S

(D0392)

for insulated pipes



Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with 2S clamp
- 2S clamp with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 110\text{mm} = 80\text{kg/m}^3$
- PIR density for $D > 110\text{mm} = 120\text{kg/m}^3$
- thermal conductivity lambda (approx. value): 0.30 W/(mK)
- temperature range $-45\text{ °C} - +105\text{ °C}$

| Product Number | Connection Thread | Total Height | Total Width | Total Length | Insulation Thickness | Maximum Allowed Load $F_{0,z}$ |
|------------------|-------------------|--------------|-------------|--------------|----------------------|--------------------------------|
| Reference letter | G | H | W | L | Is | $F_{0,z}$ |
| Unit description | | mm | mm | mm | mm | N |
| I603303012 | M8/M10 | 161 | 178 | 75 | 60 | 250 |
| I603303016 | M8/M10 | 161 | 178 | 75 | 60 | 270 |
| I603303018 | M8/M10 | 168 | 185 | 75 | 60 | 310 |
| I603303020 | M8/M10 | 168 | 185 | 75 | 60 | 320 |
| I603303022 | M8/M10 | 168 | 185 | 75 | 60 | 350 |
| I603303025 | M8/M10 | 177 | 194 | 75 | 60 | 370 |
| I603303028 | M8/M10 | 177 | 194 | 75 | 60 | 380 |
| I603303032 | M8/M10 | 177 | 194 | 75 | 60 | 390 |
| I603303035 | M8/M10 | 186 | 203 | 75 | 60 | 400 |
| I603303040 | M8/M10 | 186 | 203 | 75 | 60 | 420 |
| I603303042 | M8/M10 | 186 | 203 | 75 | 60 | 500 |
| I603303048 | M8/M10 | 199 | 217 | 75 | 60 | 530 |
| I603303050 | M8/M10 | 199 | 217 | 75 | 60 | 540 |
| I603303054 | M8/M10 | 210 | 227 | 75 | 60 | 580 |
| I603303057 | M8/M10 | 210 | 227 | 75 | 60 | 600 |
| I603303060 | M8/M10 | 210 | 227 | 75 | 60 | 620 |
| I603303064 | M8/M10 | 221 | 239 | 75 | 60 | 640 |
| I603303070 | M8/M10 | 221 | 239 | 75 | 60 | 680 |
| I603303076 | M8/M10 | 232 | 249 | 75 | 60 | 720 |
| I603303089 | M8/M10 | 243 | 260 | 75 | 60 | 730 |
| I603303102 | M8/M10 | 253 | 271 | 75 | 60 | 760 |