

## Walraven BISOFIX® PIR80 + HD500

(D0398)

for insulated pipes



### Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with HD500 clamp
- HD500 clamp with M8/M10 and M10/M12 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for  $D < 110\text{mm} = 80\text{kg/m}^3$
- PIR density for  $D > 110\text{mm} = 120\text{kg/m}^3$
- thermal conductivity lambda (approx. value):  $0.30\text{ W/(mK)}$
- product is part of the Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range  $-45\text{ °C} - +105\text{ °C}$

Product Number	Connection Thread	Total Height	Total Width	Total Length	Insulation Thickness	Maximum Allowed Load Faz
Reference letter	G	H	W	L	Is	Fa,z
Unit description		mm	mm	mm	mm	N
1803306089	M16	290	335	75	80	800
1803306100	M16	300	345	75	80	820
1803306114	M16	315	360	75	80	1,860
1803306120	M16	324	367	75	80	2,150