




## Walraven Yeti® Type A Rubberfoot Support System (BUP1000)

(10470)

for Rooftop Installations



### Features & benefits

- for supporting small pipework systems, ductwork runs, cable trays and heat pumps
- to support climate installations, walkways on flat roofs, etc.
- does not penetrate the waterproof membrane (at PVC roofs a separating layer must be installed to protect against plasticizer migration - see Walraven BIS Yeti® Triplex Separation Layer)
- material: vulcanized rubber 100% recycled material, black; strut channel 41x21mm made of steel 1.0242
- noise reduction according to DIN EN ISO 10140-1 and DIN EN ISO 10140-3 up to 33 dB(A)
- UV resistant according to EN ISO 16474-3:2014-02 certified by ITB
- Strut Channel: surface protection: product is part of the BIS UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- For a detailed calculation and for support how to spread the load please contact Walraven Technical Support.
- In cases where a foot is used in roof applications, the installer is obliged to verify maximum load capacity of roof before installation.



| Productnumber    | Total Width | Total Length | Total Height |
|------------------|-------------|--------------|--------------|
| Reference Letter | W           | L            | H            |
| Unit description | mm          | mm           | mm           |
| 67688250         | 180         | 250          | 95           |
| 67688400         | 180         | 400          | 95           |
| 67688600         | 180         | 600          | 95           |
| 67688000         | 180         | 1,000        | 95           |