

Walraven Chemical Anchor WB300

(L0391)

high performance chemical anchoring system for cracked and con-cracked concrete, masonry and rebar connections



Features & benefits

- high-performance chemical anchoring system for medium to heavy loads
- reduced concrete edge and anchor spacing distances
- always correct mixing ration thanks to static mixer nozzle
- for use with industry-standard silicone dispensing guns
- approved for threaded rods starting at grade 4.8 and above
- installations in wet and flooded holes without loss of load capacity
- cartridge may be used up over several times (each installation after a break requires new mixing nozzle)
- ETA Option 1 approval for cracked and non-cracked concrete
- ETA approval for hollow and solid masonry
- ETA TR023 for post-installed rebar connections
- seismic performance category C1 and C2 for design of anchorages under seismic action
- approved for 50 and 100 years of service life
- for loads and more information, refer to the product data sheet and/or the ETA reports
- substrate type: cracked concrete, non-cracked concrete, solid masonry, hollow masonry

Productnumber	Processing Temperature	Curing Time	Amount of Nozzles	Total Height	Total Width	Total Depth
Reference Letter				H	W	DiT
Unit description	°C	min		mm	mm	mm
6099030E	5 - 30	35 - 145	1	260	60	60
6099030W	5 - 30	35 - 145	1	260	60	60