

Walraven Mengerling® Sealing Ring

(N2005)

for pipe



Features & benefits

- easy to install (without lubricant)
- for use up to 0.5 bar internal pressure
- for connecting and sealing of cast iron pipe with socket with SML or HT/PE-pipe
- material: EPDM rubber, black
- tested according to DIN 4060

Productnumber	Model	Type	DN	Total Height	Total Width	Total Depth
Reference Letter			DN	H	W	DtT
Unit description				mm	mm	mm
7300050	GA-collar to SML or GA-Pipe	I	DN 50	20	73	73
7300070	GA-collar to SML or GA-Pipe	I	DN 70	20	95	95
7300100	GA-collar to SML or GA-Pipe	I	DN 100	20	125	125
7300125	GA-collar to SML or GA-Pipe	I	DN 125	20	155	155
7300150	GA-collar to SML or GA-Pipe	I	DN 150	20	180	180
7300200	GA-collar to SML or GA-Pipe	I	DN 200	20	220	220
7301050	GA-collar to SML or GA-Pipe	A	DN 50	10	65	65
7301070	GA-collar to SML or GA-Pipe	A	DN 70	10	90	90
7301100	GA-collar to SML or GA-Pipe	A	DN 100	10	120	120
7301125	GA-collar to SML or GA-Pipe	A	DN 125	10	155	155
7301150	GA-collar to SML or GA-Pipe	A	DN 150	15	180	180
7301200	GA-collar to SML or GA-Pipe	A	DN 200	15	220	220
7302050		IS	DN 50	20	75	75
7302125		IS	DN 125	20	145	145
7303050		AS	DN 50	15	75	75
7303070		AS	DN 70	10	95	95
7303125		AS	DN 125	17	160	160