

## Walraven Mengering® Sealing Ring

(N2005)

for pipe



### Features & benefits

- easy to install (without lubricant)
- for use up to 0.5 bar internal pressure
- for connecting and sealing of cast iron pipe with socket with SML or HT/PE-pipe
- material: EPDM rubber, black
- tested according to DIN 4060

Product Number	Model	Type	DN	Total Height	Total Width	Total Depth
Reference letter			D	H	W	DtT
Unit description				mm	mm	mm
7300050	GA-collar to SML or GA-Pipe	I	DN 50	20	73	73
7300070	GA-collar to SML or GA-Pipe	I	DN 70	20	95	95
7300100	GA-collar to SML or GA-Pipe	I	DN 100	20	125	125
7300125	GA-collar to SML or GA-Pipe	I	DN 125	20	155	155
7300150	GA-collar to SML or GA-Pipe	I	DN 150	20	180	180
7300200	GA-collar to SML or GA-Pipe	I	DN 200	20	220	220
7301050	GA-collar to SML or GA-Pipe	A	DN 50	10	65	65
7301070	GA-collar to SML or GA-Pipe	A	DN 70	10	90	90
7301100	GA-collar to SML or GA-Pipe	A	DN 100	10	120	120
7301125	GA-collar to SML or GA-Pipe	A	DN 125	10	155	155
7301150	GA-collar to SML or GA-Pipe	A	DN 150	15	180	180
7301200	GA-collar to SML or GA-Pipe	A	DN 200	15	220	220
7302050	GA-collar to HT/PE-Pipe	IS	DN 50	20	75	75
7302125	GA-collar to HT/PE-Pipe	IS	DN 125	20	145	145
7303050	GA-collar to HT/PE-Pipe	AS	DN 50	15	75	75
7303070	GA-collar to HT/PE-Pipe	AS	DN 70	10	95	95
7303125	GA-collar to HT/PE-Pipe	AS	DN 125	17	160	160