

Walraven Pacifyre® MLAR Flexmatte

(U0442)

For use according to MLAR/LAR/RbALi, Section 4.2 or 4.3 "Erleichterungen"



Features & benefits

- For sealing off pipes and cables according to MLAR/LAR/RbALi, Section 4.2 or 4.3 "Relief" in walls (solid walls and light partitions) and ceilings with fire protection requirements according to MBO or MLAR/LAR/RbALi
- Installation of connectors for cast iron pipes in walls and ceilings possible
- Non-combustible pipes up to a maximum pipe outside diameter of 160 mm
- Combustible pipes up to a maximum pipe outside diameter of 32 mm
- Small space requirement as only 1 layer is required
- Installation in complete component thickness
- Self-adhesive over the entire length, making installation quick and easy
- Recommendation: label
- Sound insulation in accordance with P-BA 108/2008 IBP or the technical statement S-10460 IBP

Productnumber	Length	Intumescent Width	Intumescent Layer Thickness	Total Height	Total Width	Total Depth
Reference Letter	<i>I</i>	<i>IW</i>	<i>ILT</i>	<i>H</i>	<i>W</i>	<i>DiT</i>
Unit description	mm	mm	mm	mm	mm	mm
2136245460	460	245	4	4	245	460