

Walraven BISOFIX® PIR60 + 2S

(D0392)

for insulated pipes



Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with 2S clamp
- 2S clamp with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 110\text{mm} = 80\text{kg/m}^3$
- PIR density for $D > 110\text{mm} = 120\text{kg/m}^3$
- thermal conductivity lambda (approx. value): 0.30 W/(mK)
- temperature range $-45\text{ °C} - +105\text{ °C}$

Product Number	Connection Thread	Total Height	Total Width	Total Length	Insulation Thickness	Maximum Allowed Load $F_{0,z}$
Reference letter	G	H	W	L	Is	$F_{0,z}$
Unit description		mm	mm	mm	mm	N
I603303012	M8/M10	161	178	75	60	250
I603303016	M8/M10	161	178	75	60	270
I603303018	M8/M10	168	185	75	60	310
I603303020	M8/M10	168	185	75	60	320
I603303022	M8/M10	168	185	75	60	350
I603303025	M8/M10	177	194	75	60	370
I603303028	M8/M10	177	194	75	60	380
I603303032	M8/M10	177	194	75	60	390
I603303035	M8/M10	186	203	75	60	400
I603303040	M8/M10	186	203	75	60	420
I603303042	M8/M10	186	203	75	60	500
I603303048	M8/M10	199	217	75	60	530
I603303050	M8/M10	199	217	75	60	540
I603303054	M8/M10	210	227	75	60	580
I603303057	M8/M10	210	227	75	60	600
I603303060	M8/M10	210	227	75	60	620
I603303064	M8/M10	221	239	75	60	640
I603303070	M8/M10	221	239	75	60	680
I603303076	M8/M10	232	249	75	60	720
I603303089	M8/M10	243	260	75	60	730
I603303102	M8/M10	253	271	75	60	760