



## Walraven WDI2L Drop-in Anchor Lipped

(L0322)

standard Drop-in Anchor with a lip collar



### Features & benefits

- simple and quick installation procedure
- collar with a lip for flush anchor setting at any hole depth
- medium load capacity
- European Technical Assessment according to EAD 330747-00-0601 (May 2018) for fastener for use in concrete for redundant non-structural systems
- European Technical Assessment according to EAD 330232-00-0601 (October 2016) for mechanical fastener for use in non-cracked concrete
- fire resistance class R30-R120 for design of anchorages under exposure to fire
- complies with VdS CEA 4001:2024-01 (08) for applications with sprinkler systems in concrete (M8-M20)
- for loads and more information, refer to the product data sheets and/or the ETA reports
- substrate type: cracked concrete, non-cracked concrete
- material: steel
- zinc plated

Product Number	Thread Size	Thread Type	Total Height	Total Width	Total Length	Drill Hole Diameter	Min. Drill Hole Depth	Standard Embedment Depth	Minimum Substrate Thickness
Reference letter	TS	TT	H	W	L	d0	h0 min	hnom	hmin
Unit description			mm	mm	mm	mm	mm	mm	mm
6103310830	M8	Metric	11	11	30	10	33	≥ 30	100