

Walraven BISOFIX® PIR20 + HD500

(D0356)

for insulated pipes



Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with HD500 clamp
- HD500 clamp with M8/M10 and M10/M12 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 110\text{mm} = 80\text{kg/m}^3$
- PIR density for $D > 110\text{mm} = 120\text{kg/m}^3$
- thermal conductivity lambda (approx. value): 0.30 W/(mK)
- product is part of the Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range $-45\text{ °C} - +105\text{ °C}$

Product Number	Connection Thread	Total Height	Total Width	Total Length	Insulation Thickness	Maximum Allowed Load Faz
Reference letter	G	H	W	L	Is	Fa,z
Unit description		mm	mm	mm	mm	N
I203304076	M10/M12	153	175	75	20	390
I203304089	M10/M12	170	193	75	20	430
I203304102	M10/M12	177	200	100	20	500
I203304108	M10/M12	191	215	100	20	1,110
I203304114	M10/M12	191	215	100	20	1,360
I203304133	M10/M12	221	254	100	20	1,410
I203304140	M10/M12	221	254	100	20	1,410
I203304160	M10/M12	240	274	100	20	1,520
I203304168	M10/M12	256	290	100	20	1,570
I203304219	M10/M12	300	345	100	20	1,620
I203304273	M10/M12	358	403	100	20	1,670