


Walraven W2000 Cushion Clamp

(H32205)

to be used for metal pipe applications



Features & benefits

- the new alternative to the Cushion Clamp
- one-piece design - no loose parts
- easier, faster, safer - installs with one hand
- 3-way screw head - Phillips, flat and hex
- unique design allows one clamp to fit multiple pipe sizes - less items to stock
- W Series Clamps are boxed for easy handling - no more bags
- material: steel 1.0242
- surface treatment: high grade Zn-Mg based coating (600 hours salt spray)
- black EPDM rubber lining protects against galvanic corrosion
- noise/vibration insulating lining
- age resistant lining
- 2016-SG-Bauakustik-1647-001-16
- UL 1565 Listed

Product Number	Outside Pipe Diameter	Pipe Diameter IPS	Pipe Diameter CTS	Pipe Diameter ACR	Total Height	Total Width	Total Depth	Material Width	Material Thickness	Maximum Allowed Load Faz
Reference Letter	D	D (IPS)	D (CTS)	D (ACR)	H	W	DtT	MW	MT	F _{0,z}
Unit description	mm	"	"	"	mm	mm	mm	mm	mm	N
2025004	9 - 10		1/4	3/8	56	42	41	41	1.25	890
2025008	14 - 16	1/4	1/2	5/8	55.3	42	47	41	1.25	890
2025010	17 - 19	3/8	5/8	3/4	59.2	42	47	41	1.25	980
2025012	20 - 22	1/2	3/4	7/8	61.9	42	47	41	1.25	980
2025014	25 - 29	3/4	1	1 1/8	68.5	42	47	41	1.50	1,780
2025016	32 - 35	1	1 1/4	1 3/8	74.1	42	47	41	1.50	1,780
2025020	40 - 43		1 1/2	1 5/8	81.3	45	47	41	1.75	1,780
2025022	48 - 50	1 1/2			88.8	45	47	41	1.75	1,780
2025024	54 - 56		2	2 1/8	94	45	47	41	1.75	1,780
2025026	60 - 63	2			103.4	45	47	41	1.75	1,780