


Walraven Threaded Rod (BUP1000)

(K5508)

for threaded connections, hangers and ties,



Features & benefits

- according to DIN 976-1
- material: steel, strength class 4.8
- product is part of the Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- thread with 60° angle provides best performance
- M10 and M12 tested for fire safety according to EN 1363-1



Product Number	RSK Number	Norm / Standard	Thread Size	Total Length	Total Height	Total Width
<i>Reference letter</i>			<i>TS</i>	<i>L</i>	<i>H</i>	<i>W</i>
<i>Unit description</i>				<i>mm</i>	<i>mm</i>	<i>mm</i>
63081008	3821404	DIN 976-1	M8	1,000	8	8
63081010	3821405	DIN 976-1	M10	1,000	10	10
63081012	3821406	DIN 976-1	M12	1,000	12	12
63081016	3821533	DIN 976-1	M16	1,000	16	16
63082008	3821407	DIN 976-1	M8	2,000	8	8
63082010	3821408	DIN 976-1	M10	2,000	10	10
63082012	3821409	DIN 976-1	M12	2,000	12	12
63082016	3821534	DIN 976-1	M16	2,000	16	16