

Walraven Chemical Anchor WB300

(L0391)

high performance chemical anchoring system for cracked and con-cracked concrete, masonry and rebar connections



Features & benefits

- high-performance chemical anchoring system for medium to heavy loads
- reduced concrete edge and anchor spacing distances
- always correct mixing ration thanks to static mixer nozzle
- for use with industry-standard silicone dispensing guns
- approved for threaded rods starting at grade 4.8 and above
- installations in wet and flooded holes without loss of load capacity
- cartridge may be used up over several times (each installation after a break requires new mixing nozzle)
- ETA Option 1 approval for cracked and non-cracked concrete
- ETA approval for hollow and solid masonry
- ETA TR023 for post-installed rebar connections
- seismic performance category C2 for design of anchorages under seismic action
- approved for 50 and 100 years of service life
- for loads and more information, refer to the product data sheet and/or the ETA reports
- substrate type: cracked concrete, non-cracked concrete, solid masonry, hollow masonry

Product Number	RSK Number	Cartridge Volume	Amount of Nozzles	Total Height	Total Width	Total Depth
<i>Reference letter</i>				<i>H</i>	<i>W</i>	<i>DeT</i>
<i>Unit description</i>		<i>ml</i>		<i>mm</i>	<i>mm</i>	<i>mm</i>
6099030W	4450319	300	1	260	60	60