

## Walraven BISOFIX® E13 + HD500

(D0308)

for insulated pipes



### Features & benefits

- for combination with elastomeric foam insulation
- vapourproof glueable with pipe insulation
- insulating pipe support with HD500 clamp
- HD500 clamp with M8/M10 and M10/M12 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for  $D < 80\text{mm} = 80\text{kg/m}^3$
- PIR density for  $D > 80\text{mm} = 120\text{kg/m}^3$
- product is part of the Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range  $-45\text{ °C} - +105\text{ °C}$

| Product Number   | Outside Pipe Diameter | Connection Thread | Total Height | Total Width | Total Length | Insulation Thickness | Maximum Allowed Load |
|------------------|-----------------------|-------------------|--------------|-------------|--------------|----------------------|----------------------|
| Reference Letter | <i>D</i>              | <i>G</i>          | <i>H</i>     | <i>W</i>    | <i>L</i>     | <i>Is</i>            | <i>Fa,z</i>          |
| Unit description | <i>mm</i>             |                   | <i>mm</i>    | <i>mm</i>   | <i>mm</i>    | <i>mm</i>            | <i>N</i>             |
| I133304076       | 76.1                  | M10/M12           | 153          | 193         | 50           | 16.3                 | 575                  |
| I133304102       | 101.6                 | M10/M12           | 177          | 200         | 50           | 16.3                 | 1,000                |
| I133304160       | 159 - 160             | M10/M12           | 240          | 274         | 100          | 16.3                 | 1,950                |