


Walraven BISOFIX® PIR30 (40mm) + 2S

(D0363)

for insulated pipes



Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with 2S clamp
- 2S clamp with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 110\text{mm}$ = 80kg/m^3
- PIR density for $D > 110\text{mm}$ = 120kg/m^3
- thermal conductivity lambda (approx. value): 0.30 W/(mK)
- zinc plated
- temperature range $-45\text{ °C} - +105\text{ °C}$

Product Number	Outside Pipe Diameter	Connection Thread	Total Height	Total Width	Total Length	Insulation Thickness	Maximum Allowed Load Faz
Reference Letter	D	G	H	W	L	Is	Fa,z
Unit description	mm		mm	mm	mm	mm	N
I343303022	21.3 - 22	M8/M10	109	124	40	40	230
I343303028	26.9 - 28	M8/M10	119	136	40	40	300
I343303034	33.7 - 35	M8/M10	119	136	40	40	320
I343303042	42.4	M8/M10	127	143	40	40	350
I343303048	48.3	M8/M10	136	153	40	40	370
I343303054	54	M8/M10	136	153	40	40	380
I343303060	60.3	M8/M10	151	168	40	40	410
I343303064	64	M8/M10	151	168	40	40	420
I343303076	76.1	M8/M10	161	178	40	40	460
I343303089	88.9	M8/M10	177	194	40	40	500
I343303114	114.3	M8/M10	210	227	40	40	1,370