


Walraven BISOFIX® PIR30 + HD500

(D0366)

for insulated pipes



Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with HD500 clamp
- HD500 clamp with M8/M10 and M10/M12 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 110\text{mm}$ = 80kg/m^3
- PIR density for $D > 110\text{mm}$ = 120kg/m^3
- thermal conductivity λ (approx. value): 0.30 W/(mK)
- product is part of the Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range -45 °C - $+105\text{ °C}$

Product Number	Outside Pipe Diameter	Connection Thread	Total Height	Total Width	Total Length	Insulation Thickness	Maximum Allowed Load Faz
Reference Letter	D	G	H	W	L	Is	Fa,z
Unit description	mm		mm	mm	mm	mm	N
I303304076	76.1	M10/M12	177	200	75	30	460
I303304089	88.9	M10/M12	191	215	75	30	500
I303304102	101.6	M10/M12	207	240	100	30	550
I303304114	114.3	M10/M12	221	254	100	30	1,370
I303304133	133	M10/M12	240	274	100	30	1,520
I303304140	139.7	M10/M12	240	274	100	30	1,570
I303304160	159 - 160	M10/M12	256	290	100	30	1,720
I303304168	168.3	M10/M12	265	299	100	30	2,720
I303304273	273.1	M10/M12	358	403	150	30	5,020
I303304324	323.9	M10/M12	424	468	150	30	5,790