


Walraven BISOFIX® PIR40 (40mm) + 2S

(D0373)

for insulated pipes



Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with 2S clamp
- 2S clamp with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 110\text{mm}$ = 80kg/m^3
- PIR density for $D > 110\text{mm}$ = 120kg/m^3
- thermal conductivity λ (approx. value): 0.30 W/(mK)
- clamp: zinc plated
- temperature range $-45\text{ °C} - +105\text{ °C}$

Product Number	Outside Pipe Diameter	Connection Thread	Total Height	Total Width	Total Length	Insulation Thickness
Reference Letter	<i>D</i>	<i>G</i>	<i>H</i>	<i>W</i>	<i>L</i>	<i>Is</i>
Unit description	<i>mm</i>		<i>mm</i>	<i>mm</i>	<i>mm</i>	<i>mm</i>
I443303042	42.4	M8/M10	151	168	40	40
I443303048	48.3	M8/M10	161	178	40	40
I443303060	60.3	M8/M10	168	185	40	40
I443303076	76	M8/M10	186	203	40	40
I443303089	88.9	M8/M10	199	217	40	40