

Walraven W5000 Cushion Clamp

(H32210)

to be used for plastic pipe applications



EPD

Features & benefits

- the new alternative to the Cushion Clamp
- with removable spacer washers, making the clamp suitable for either sliding or anchoring
- one-piece design - no loose parts
- easier, faster, safer - installs with one hand
- 3-way screw head - Phillips, flat and hex
- W Series Clamps are boxed for easy handling - no more bags
- material: steel 1.0242
- surface treatment: high grade Zn-Mg based coating (600 hours salt spray)
- green EPDM rubber lining will prevent plasticiser migration
- noise/vibration insulating lining according DIN EN ISO 3822-1
- age resistant lining
- UL 1565 Listed
- 2016-SG-Bauakustik-1647-001-16
- 2016-TR151002-V5

Product Number	Outside Pipe Diameter	Total Height	Total Width	Total Depth	Material Width	Material Thickness	Key Driver Size
Reference Letter	D	H	W	DtT	MW	MT	Drive
Unit description	mm	mm	mm	mm	mm	mm	
2055007		55.3	42	46	41	1.25	
2055008	14 - 16	55.3	42	46	41	1.25	WAF 3/8"
2055009		55.3	42	46	41	1.25	
2055010	17 - 19	59.2	42	46	41	1.25	WAF 3/8"
2055012	20 - 22	61.9	42	46	41	1.25	WAF 3/8"
2055013	24 - 25	68.5	42	46	41	1.50	WAF 3/8"
2055014	25 - 29	68.5	42	46	41	1.50	WAF 3/8"
2055016	32 - 35	74.1	42	46	41	1.50	WAF 3/8"
2055020	40 - 43	81.3	45	46	41	1.75	WAF 3/8"
2055022	48 - 50	88.8	45	46	41	1.75	WAF 3/8"
2055023	50 - 52	94	45	46	41	1.75	WAF 3/8"
2055024		94	45	46	41	1.75	WAF 3/8"
2055025	56 - 58	103.4	45	46	41	1.75	WAF 3/8"
2055026	60 - 63	103.4	45	46	41	1.75	WAF 3/8"