


Walraven Pacifyre® SML-MI fire protection set

(U0443)

For fire protection of cast iron pipes in mixed penetrations



Features & benefits

- For sealing cast iron pipes in R90 quality according to DIN 4102-11 only in solid ceilings with fire protection requirements according to MBO or MLAR/LAR/RbALi and R90 pipe seals in F90 components
- Zero distance to seals with Pacifyre® IWM III fire protection bandage, Pacifyre® EFC fire protection sleeve and Pacifyre® M pipe jacketing as well as to metal pipes with rock wool ($\geq 80 \text{ kg/m}^3$) (Type RS 800)
- No additional shafts necessary in basement rooms
- Easy processing and high flexibility thanks to self-adhesive mat
- Multiplicable seals can be installed with a distance of just 50 mm
- Transition from cast to plastic pipe possible directly after the branch
- Transition to plastic pipe up to max. 110 mm
- Molded parts and connectors in the component are permitted, but must be wrapped
- Possible branches 45° or 88° degrees
- Dimensions of fire protection mat: H 245 x W 460 x 3 mm
- Dimensions of insulating mat: H 250 x W 620 x 30 mm
- Sound insulation test certificate (P-BA 108/2008) from IBP (Fraunhofer Inst.)
- General type approval (aBG) Z-19.53-2388 from the German Institute for Building Technology (DIBt)
- Approved by the German Institute for Construction Technology (DIBt) according to Z-19.17-2114 and is externally monitored by an MPA
- Approved by the German Institute for Construction Technology (DIBt) according to Z-19.17-2114 and is externally monitored by an MP

Product Number	Outside Pipe Diameter	Outer Diameter	Total Height	Total Width	Total Depth
Reference Letter	D	OD	H	W	DtT
Unit description	mm	mm	mm	mm	mm
2136200050	50	104	280	266	400
2136200080	70 - 80	125	280	266	400
2136200100	100	157	280	266	400