


Walraven IH126K Phenolic Insulation Block 15 mm Thick

(D1005)

for steel, copper and plastic pipe



Features & benefits

- load bearing insulation ring for steel, copper and plastic pipe
- metal spreader plate recommended above 50 NB
- foil covered
- manufactured from High Density Phenolic Foam
- negligible water absorption
- does not contain CFC's and HCFC's
- K value 0.030 to 0.037 W/(mK) at 10 °C
- thermal conductivity determined by testing cylindrical specimen according to BS EN ISO 8497
- reaction to fire: BL-s1 d0
- density: <111mm OD pipe, 60kgs/m3
- density: 111mm to 169mm OD pipe, 80kgs/m3
- temperature resistance from -50 °C to +110 °C



Product Number	Outside Pipe Diameter	DN	Total Height	Total Width	Total Length	Material Thickness	Operating Temperature	Maximum Allowed Load Faz
Reference Letter	D	D	H	W	L	MT	CEL	F _{0,z}
Unit description	mm		mm	mm	mm	mm		N
8901015015	15		45	45	90	15.00	-50 - 110	120
8901015021	22	DN 15	51	51	90	15.00	-50 - 110	176
8901015027	28	DN 20	57	57	90	15.00	-50 - 110	224
8901015034	35	DN 25	64	64	90	15.00	-50 - 110	280
8901015042	42	DN 32	72	72	90	15.00	-50 - 110	337
8911015048	48	DN 40	78	78	90	15.00	-50 - 110	387
8911015054	54		84	84	90	15.00	-50 - 110	433
8911015060	60	DN 50	90	90	90	15.00	-50 - 110	481
8911015066	66		96	96	90	15.00	-50 - 110	529
8911015076	76	DN 65	106	106	90	15.00	-50 - 110	609
8911015114	114	DN 100	144	144	90	15.00	-50 - 110	1,827
8911015140	139	DN 125	170	170	90	15.00	-50 - 110	2,243
8901015017	17	DN 10	47	47	90	15.00	-50 - 110	136
8901015020	20	DN 15	50	50	90	15.00	-50 - 110	160
8901015025	25	DN 20	55	55	90	15.00	-50 - 110	200