


Walraven W-LX-M Concrete Screw

(L0358)

zinc-plated concrete screw with M8 external thread connection and torx nut E7



Features & benefits

- very high load capacity
- approved for use in precast prestressed hollow core slabs
- up to 3 anchoring depths provide maximum installation and design flexibility
- reduced edge and anchor spacing distances
- removable
- unique tip and thread geometry prevents concrete spalling
- material: steel
- zinc plated
- fire resistance class R30-R120 for design of anchorages under exposure to fire
- complies with VdS CEA 4001:2014-04 (05) and VdS CEA 4001:2018-01 (06) for applications with sprinkler systems in concrete elements
- substrate type: cracked concrete, non-cracked concrete, precast pre-stressed hollow core slabs
- for loads and more information, refer to the product data sheets and/or the ETA reports



Productnumber	Connection Thread	Connection Height	Screw Length	Anchor Size	Key Driver Size	Nominal Head Height	Drill Hole Diameter	Total Height	Total Length	Total Width
Reference Letter	G	Gh	Is	Size	Drive	HH,n	d0	H	L	W
Unit description		mm	mm			mm	mm	mm	mm	mm
62434305	M8	25.5	55	6	E7	7	6	8	83	8
62434304	M8	25.5	35	6	E7	7	6	8	63	8