


Walraven starQuick® Clamp (White)

(C0510)

for securing conduits and pipes to walls, floors, or ceilings



Features & benefits

- one-part clamp
- clamp closes by applying pressure to the pipe
- for outdoor use and installations in swimming pool environments, chemical factories, zinc factories, etc.
- due to a patented profile it is possible to tack several clamps to each other
- material: modified PA6 (polyamide), white (according to RAL 9003)
- resistant to UV, ageing, oil and petrol
- no corrosion, recyclable, halogen free
- temperature resistance from approx. -40 °C to approx. +90 °C (constant); short to approx. +130 °C



kiwa

Product Number	Outside Pipe Diameter	Total Width x Total Height x Total Depth	Clamp Center Distance Height	Height	Connection Thread	Maximum Allowed Load Faz	Breaking Load Fbz
Reference letter	D	W x H x DtT	hlc	h	G	Fa,z	Fb,z
Unit description	(mm)	(mm) x (mm) x (mm)	(mm)	(mm)		(N)	(N)
0855010	10 - 12	29 x 27 x 17	24	12.10	None	500	500
0855012	12 - 14	29 x 27 x 17	25	10.60	None	180	550
0855015	14 - 16	29 x 29 x 17	25	10.60	None	200	600
0855018	16 - 20	29 x 31 x 17	27	10.60	None	230	700
0855022	20 - 23	29 x 33 x 17	28	10.60	None	270	800
0855028	24 - 28	40 x 54 x 17	32	10.60	None	280	850
0855031	28 - 32	40 x 60 x 17	36	10.60	None	300	900
0855035	32 - 35	43 x 65 x 17	37	10.60	None	330	1000
0855038	35 - 40	43 x 64 x 17	44	10.60	None	330	1100
0855042	40 - 44	52 x 78 x 17	44	12.10	None	330	1200
0855050	44 - 50	57 x 87 x 17	50	12.10	None	330	1300
0855054	48 - 55	63 x 90 x 20	50	12.10	None	330	1400
0855063	59 - 95	74 x 94 x 20	57	12.10	None	500	1500