

Walraven BISOFIX® E13 + 2S

(D0304)

for insulated pipes



Features & benefits

- for combination with elastomeric foam insulation
- vapourproof glueable with pipe insulation
- insulating pipe support with 2S clamp
- 2S clamp with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 80\text{mm}$ = 80kg/m^3
- PIR density for $D \geq 80\text{mm}$ = 120kg/m^3
- temperature range $-45\text{ }^{\circ}\text{C}$ - $+105\text{ }^{\circ}\text{C}$

Product Number	Outside Pipe Diameter	Connection Thread	Total Width x Total Height x Insulation Thickness Total Length		Maximum Allowed Load $F_{a,z}$
Reference letter	D	G	W x H x L	Is	$F_{a,z}$
Unit description	(mm)		(mm) x (mm) x (mm)	(mm)	(N)
I133303008	8	M8/M10	69 x 58 x 50	13.30	100
I133303010	10.20	M8/M10	69 x 58 x 50	13.30	100
I133303012	12	M8/M10	78 x 68 x 50	13.30	100
I133303015	15	M8/M10	78 x 68 x 50	13.30	100
I133303018	17.20 - 18	M8/M10	78 x 68 x 50	13.30	100
I133303022	21.30 - 22	M8/M10	84 x 74 x 50	13.50	100
I133303028	26.90 - 28	M8/M10	93 x 83 x 50	13.30	100
I133303035	33.70 - 35	M8/M10	99 x 89 x 50	13.30	100
I133303042	42.40	M8/M10	111 x 96 x 50	13.30	150
I133303048	48.30	M8/M10	118 x 103 x 50	13.30	225
I133303054	54	M8/M10	124 x 109 x 50	13.30	225
I133303057	57	M8/M10	124 x 109 x 50	13.30	350
I133303060	60.30	M8/M10	136 x 119 x 50	13.90	350
I133303064	64	M8/M10	143 x 127 x 50	18	350
I133303070	70	M8/M10	143 x 127 x 50	16.30	425
I133303076	76.10	M8/M10	153 x 136 x 50	16.30	575
I133303089	88.90	M8/M10	168 x 151 x 50	17.90	875
I133303102	101.60	M8/M10	178 x 161 x 50	16.30	1000
I133303108	108	M8/M10	185 x 168 x 50	16.30	1075
I133303114	114.30	M8/M10	194 x 177 x 50	18.90	1250
I133303133	133	M8/M10	217 x 199 x 100	16.30	1475
I133303140	139.70	M8/M10	227 x 210 x 100	18.20	1700
I133303160	159 - 160	M8/M10	239 x 221 x 100	16.30	1950
I133303168	168.30	M8/M10	249 x 232 x 100	16.30	2125