

Walraven BISOFIX® E13 + Bifix® G2

(D0306)

for insulated pipes



Features & benefits

- for combination with elastomeric foam insulation
- vapourproof glueable with pipe insulation
- insulating pipe support with Bifix® G2 clamp
- Bifix® G2 with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 80\text{mm}$ = 80kg/m^3
- PIR density for $D \geq 80\text{mm}$ = 120kg/m^3
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range $-45\text{ }^{\circ}\text{C}$ - $+105\text{ }^{\circ}\text{C}$

Product Number	Outside Pipe Diameter	Connection Thread	Total Width x Total Height x Insulation Thickness Total Length		Maximum Allowed Load $F_{a,z}$
Reference letter	D	G	W x H x L	Is	$F_{a,z}$
Unit description	(mm)		(mm) x (mm) x (mm)	(mm)	(N)
I133008008	8	M8/M10	80 x 62 x 50	13.30	100
I133008010	10.20	M8/M10	80 x 62 x 50	13.30	100
I133008012	12	M8/M10	80 x 62 x 50	13.30	100
I133008015	15	M8/M10	84 x 66 x 50	13.30	100
I133008018	17.20 - 18	M8/M10	84 x 66 x 50	13.30	100
I133008022	21.30 - 22	M8/M10	91 x 73 x 50	13.50	100
I133008028	26.90 - 28	M8/M10	97 x 79 x 50	13.30	100
I133008035	33.70 - 35	M8/M10	104 x 86 x 50	13.30	100
I133008042	42.40	M8/M10	110 x 92 x 50	13.30	150
I133008048	48.30	M8/M10	118 x 100 x 50	13.30	225
I133008054	54	M8/M10	125 x 107 x 50	13.30	225
I133008057	57	M8/M10	125 x 107 x 50	13.30	350
I133008060	60.30	M8/M10	134 x 115 x 50	13.90	350
I133008064	64	M8/M10	148 x 129 x 50	18	350
I133008070	70	M8/M10	148 x 129 x 50	16.30	425
I133008076	76.10	M8/M10	155 x 137 x 50	16.30	575
I133008089	88.90	M8/M10	172 x 154 x 50	17.90	875
I133008102	101.60	M8/M10	181 x 162 x 50	16.30	1000
I133008108	108	M8/M10	181 x 162 x 50	16.30	1075
I133008114	114.30	M8/M10	201 x 183 x 50	18.90	1250
I133008133	133	M8/M10	217 x 195 x 100	16.30	1475
I133008140	139.70	M8/M10	229 x 208 x 100	18.20	1700
I133008160	159 - 160	M8/M10	248 x 227 x 100	16.30	1950
I133008168	168.30	M8/M10	248 x 227 x 100	16.30	2125