

Walraven BISOFIX® E13 + HD500

(D0308)

for insulated pipes



Features & benefits

- for combination with elastomeric foam insulation
- vapourproof glueable with pipe insulation
- insulating pipe support with HD500 clamp
- HD500 clamp with M8/M10 and M10/M12 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 80\text{mm}$ = 80kg/m^3
- PIR density for $D \geq 80\text{mm}$ = 120kg/m^3
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range $-45\text{ }^{\circ}\text{C}$ - $+105\text{ }^{\circ}\text{C}$

Product Number	Outside Pipe Diameter	Connection Thread	Total Width x Total Height x Insulation Thickness Total Length		Maximum Allowed Load $F_{a,z}$
Reference letter	<i>D</i>	<i>G</i>	<i>W x H x L</i>	<i>Is</i>	<i>F_{a,z}</i>
Unit description	(mm)		(mm) x (mm) x (mm)	(mm)	(N)
I133304076	76.10	M10/M12	193 x 153 x 50	16.30	575
I133304089	88.90	M10/M12	200 x 170 x 50	17.90	875
I133304102	101.60	M10/M12	200 x 177 x 50	16.30	1000
I133304108	108	M10/M12	215 x 177 x 50	16.30	1075
I133304114	114.30	M10/M12	240 x 191 x 50	18.90	1250
I133304133	133	M10/M12	254 x 207 x 100	16.30	1475
I133304140	139.70	M10/M12	274 x 221 x 100	18.20	1700
I133304160	159 - 160	M10/M12	274 x 240 x 100	16.30	1950
I133304168	168.30	M10/M12	274 x 240 x 100	16.30	2125