

Walraven BISOFIX® E19 + 2S

(D0316)

for insulated pipes



Features & benefits

- for combination with elastomeric foam insulation
- vapourproof glueable with pipe insulation
- insulating pipe support with 2S clamp
- 2S clamp with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 80\text{mm}$ = 80kg/m^3
- PIR density for $D \geq 80\text{mm}$ = 120kg/m^3
- temperature range $-45\text{ }^{\circ}\text{C}$ - $+105\text{ }^{\circ}\text{C}$

Product Number	Outside Pipe Diameter	Connection Thread	Total Width x Total Height x Insulation Thickness Total Length		Maximum Allowed Load $F_{a,z}$
Reference letter	D	G	W x H x L	Is	$F_{a,z}$
Unit description	(mm)		(mm) x (mm) x (mm)	(mm)	(N)
I193303012	12	M8/M10	84 x 74 x 50	19.30	100
I193303015	15	M8/M10	93 x 83 x 50	19.50	100
I193303018	17.20 - 18	M8/M10	93 x 83 x 50	19.30	100
I193303022	21.30 - 22	M8/M10	93 x 83 x 50	19.30	100
I193303028	26.90 - 28	M8/M10	99 x 89 x 50	19.30	100
I193303035	33.70 - 35	M8/M10	118 x 103 x 50	19.30	100
I193303042	42.40	M8/M10	118 x 103 x 50	19.30	150
I193303048	48.30	M8/M10	136 x 119 x 50	19.30	225
I193303054	54	M8/M10	143 x 127 x 50	23	225
I193303057	57	M8/M10	143 x 127 x 50	23	225
I193303060	60.30	M8/M10	143 x 127 x 50	19.90	350
I193303064	64	M8/M10	153 x 136 x 50	25.30	350
I193303070	70	M8/M10	168 x 151 x 50	27.30	452
I193303076	76.10	M8/M10	168 x 151 x 50	25.30	575
I193303089	88.90	M8/M10	185 x 168 x 50	25.30	875
I193303102	101.60	M8/M10	194 x 177 x 50	25.30	1000
I193303108	108	M8/M10	203 x 186 x 50	25.30	1075
I193303114	114.30	M8/M10	217 x 199 x 50	25.30	1250
I193303133	133	M8/M10	239 x 221 x 100	26.20	1475
I193303140	139.70	M8/M10	239 x 221 x 100	25.30	1700
I193303160	159 - 160	M8/M10	260 x 243 x 100	25.30	1950
I193303168	168.30	M8/M10	271 x 253 x 100	25.30	2125