

Walraven BISOFIX® E25 + HD500

(D0332)

for insulated pipes



Features & benefits

- for combination with elastomeric foam insulation
- vapourproof glueable with pipe insulation
- insulating pipe support with HD500 clamp
- HD500 clamp with M8/M10 and M10/M12 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 80\text{mm} = 80\text{kg/m}^3$
- PIR density for $D > 80\text{mm} = 120\text{kg/m}^3$
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range $-45\text{ }^{\circ}\text{C} - +105\text{ }^{\circ}\text{C}$

Product Number	Outside Pipe Diameter	Connection Thread	Total Width x Total Height x Insulation Thickness Total Length		Maximum Allowed Load $F_{a,z}$
Reference letter	<i>D</i>	<i>G</i>	<i>W x H x L</i>	<i>Is</i>	<i>F_{a,z}</i>
Unit description	(mm)		(mm) x (mm) x (mm)	(mm)	(N)
I253304108	108	M10/M12	254 x 221 x 50	34	1075
I253304219	219.10	M16	367 x 324 x 100	32.30	3525