


Walraven BISOFIX® PIR30 (40mm) + 2S

(D0363)

for insulated pipes



Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with 2S clamp
- 2S clamp with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 110\text{mm}$ = 80kg/m^3
- PIR density for $D \geq 110\text{mm}$ = 120kg/m^3
- zinc plated
- temperature range $-45\text{ }^{\circ}\text{C}$ - $+105\text{ }^{\circ}\text{C}$

Product Number	Outside Pipe Diameter	Connection Thread	Total Width x Total Height x Insulation Thickness Total Length		Maximum Allowed Load $F_{a,z}$
Reference letter	D	G	W x H x L	Is	$F_{a,z}$
Unit description	(mm)		(mm) x (mm) x (mm)	(mm)	(N)
I343303022	21.30 - 22	M8/M10	124 x 109 x 40	40	230
I343303028	26.90 - 28	M8/M10	136 x 119 x 40	40	300
I343303034	33.70 - 35	M8/M10	136 x 119 x 40	40	320
I343303042	42.40	M8/M10	143 x 127 x 40	40	350
I343303048	48.30	M8/M10	153 x 136 x 40	40	370
I343303054	54	M8/M10	153 x 136 x 40	40	380
I343303060	60.30	M8/M10	168 x 151 x 40	40	410
I343303064	64	M8/M10	168 x 151 x 40	40	420
I343303076	76.10	M8/M10	178 x 161 x 40	40	460
I343303089	88.90	M8/M10	194 x 177 x 40	40	500
I343303114	114.30	M8/M10	227 x 210 x 40	40	1370