

Walraven BISOFIX® PIR30 + Bifix® G2

(D0364)

for insulated pipes



Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with Bifix® G2 clamp
- Bifix® G2 with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 110\text{mm}$ = 80kg/m^3
- PIR density for $D \geq 110\text{mm}$ = 120kg/m^3
- product is part of the Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range $-45\text{ }^{\circ}\text{C}$ - $+105\text{ }^{\circ}\text{C}$

Product Number	Outside Pipe Diameter	Connection Thread	Total Width x Total Height x Insulation Thickness Total Length		Maximum Allowed Load $F_{a,z}$
Reference letter	<i>D</i>	<i>G</i>	<i>W x H x L</i>	<i>Is</i>	<i>F_{a,z}</i>
Unit description	(mm)		(mm) x (mm) x (mm)	(mm)	(N)
I303008015	15 - 16	M8/M10	118 x 100 x 75	30	170
I303008018	17.20 - 18	M8/M10	118 x 100 x 75	30	190