


Walraven BISOFIX® PIR40 + 2S

(D0372)

for insulated pipes



Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with 2S clamp
- 2S clamp with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D \leq 110\text{mm}$ = 80kg/m^3
- PIR density for $D > 110\text{mm}$ = 120kg/m^3
- clamp: zinc plated
- temperature range $-45\text{ }^{\circ}\text{C}$ - $+105\text{ }^{\circ}\text{C}$

Product Number	Outside Pipe Diameter	Connection Thread	Total Width x Total Height x Insulation Thickness Total Length		Maximum Allowed Load $F_{a,z}$
Reference letter	D	G	W x H x L	Is	$F_{a,z}$
Unit description	(mm)		(mm) x (mm) x (mm)	(mm)	(N)
I403303012	12	M8/M10	136 x 119 x 75	40	300
I403303015	15 - 16	M8/M10	136 x 119 x 75	40	320
I403303018	17.20 - 18	M8/M10	143 x 127 x 75	40	340
I403303020	20	M8/M10	143 x 127 x 75	40	340
I403303022	21.30 - 22	M8/M10	143 x 127 x 75	40	350
I403303025	25	M8/M10	153 x 136 x 75	40	350
I403303028	26.90 - 28	M8/M10	153 x 136 x 75	40	350
I403303032	32	M8/M10	153 x 136 x 75	40	370
I403303034	33.70 - 35	M8/M10	153 x 136 x 75	40	370
I403303040	40	M8/M10	168 x 151 x 75	40	400
I403303042	42.40	M8/M10	168 x 151 x 75	40	410
I403303048	48.30	M8/M10	178 x 161 x 75	40	430
I403303054	54	M8/M10	178 x 161 x 75	40	440
I403303057	56 - 57	M8/M10	178 x 161 x 75	40	460
I403303060	60.30	M8/M10	185 x 168 x 75	40	470
I403303064	64	M8/M10	185 x 168 x 75	40	490
I403303070	70	M8/M10	194 x 177 x 75	40	510
I403303076	76.10	M8/M10	203 x 186 x 75	40	530
I403303089	88.90	M8/M10	217 x 199 x 75	40	620
I403303102	101.60	M8/M10	227 x 210 x 100	40	650
I403303108	108	M8/M10	239 x 221 x 100	40	690
I403303114	114.30	M8/M10	239 x 221 x 100	40	1560
I403303133	133	M8/M10	260 x 243 x 100	40	1670
I403303140	139.70	M8/M10	271 x 253 x 100	40	1730