


Walraven BISOFIX® PIR40 (40mm) + 2S

(D0373)

for insulated pipes



Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with 2S clamp
- 2S clamp with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 110\text{mm}$ = 80kg/m^3
- PIR density for $D \geq 110\text{mm}$ = 120kg/m^3
- clamp: zinc plated
- temperature range $-45\text{ }^{\circ}\text{C}$ - $+105\text{ }^{\circ}\text{C}$

Product Number	Outside Pipe Diameter	Connection Thread	Total Width x Total Height x Total Length	Insulation Thickness
Reference letter	<i>D</i>	<i>G</i>	<i>W x H x L</i>	<i>Is</i>
Unit description	(mm)		(mm) x (mm) x (mm)	(mm)
I443303042	42.40	M8/M10	168 x 151 x 40	40
I443303048	48.30	M8/M10	178 x 161 x 40	40
I443303060	60.30	M8/M10	185 x 168 x 40	40
I443303076	76	M8/M10	203 x 186 x 40	40
I443303089	88.90	M8/M10	217 x 199 x 40	40