

## Walraven BISOFIX® PIR40 + Bifix® G2

(D0374)

for insulated pipes



### Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with Bifix® G2 clamp
- Bifix® G2 with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for  $D < 110\text{mm}$  =  $80\text{kg/m}^3$
- PIR density for  $D \geq 110\text{mm}$  =  $120\text{kg/m}^3$
- product is part of the Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range  $-45\text{ }^{\circ}\text{C}$  -  $+105\text{ }^{\circ}\text{C}$

| Product Number   | Outside Pipe Diameter | Connection Thread | Total Width x Total Height x Insulation Thickness<br>Total Length |           | Maximum Allowed Load $F_{a,z}$ |
|------------------|-----------------------|-------------------|-------------------------------------------------------------------|-----------|--------------------------------|
| Reference letter | <i>D</i>              | <i>G</i>          | <i>W x H x L</i>                                                  | <i>Is</i> | <i>F<sub>a,z</sub></i>         |
| Unit description | (mm)                  |                   | (mm) x (mm) x (mm)                                                | (mm)      | (N)                            |
| I403008022       | 21.30 - 22            | M8/M10            | 148 x 129 x 75                                                    | 40        | 230                            |
| I403008028       | 26.90 - 28            | M8/M10            | 155 x 137 x 75                                                    | 40        | 350                            |
| I403008048       | 48.30                 | M8/M10            | 172 x 154 x 75                                                    | 40        | 430                            |
| I403008060       | 60.30                 | M8/M10            | 181 x 162 x 75                                                    | 40        | 470                            |