


Walraven BISOFIX® PIR60 + 2S

(D0392)

for insulated pipes



Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with 2S clamp
- 2S clamp with M8/M10 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for $D < 110\text{mm}$ = 80kg/m^3
- PIR density for $D \geq 110\text{mm}$ = 120kg/m^3
- temperature range $-45\text{ }^{\circ}\text{C}$ - $+105\text{ }^{\circ}\text{C}$

Product Number	Outside Pipe Diameter	Connection Thread	Total Width x Total Height x Insulation Thickness Total Length		Maximum Allowed Load $F_{a,z}$
Reference letter	D	G	W x H x L	Is	$F_{a,z}$
Unit description	(mm)		(mm) x (mm) x (mm)	(mm)	(N)
I603303012	12	M8/M10	178 x 161 x 75	60	250
I603303016	15 - 16	M8/M10	178 x 161 x 75	60	270
I603303018	17.20 - 18	M8/M10	185 x 168 x 75	60	310
I603303020	20	M8/M10	185 x 168 x 75	60	320
I603303022	21.30 - 22	M8/M10	185 x 168 x 75	60	350
I603303025	25	M8/M10	194 x 177 x 75	60	370
I603303028	26.90 - 28	M8/M10	194 x 177 x 75	60	380
I603303032	32	M8/M10	194 x 177 x 75	60	390
I603303035	33.70 - 35	M8/M10	203 x 186 x 75	60	400
I603303040	40	M8/M10	203 x 186 x 75	60	420
I603303042	42.40	M8/M10	203 x 186 x 75	60	500
I603303048	48.30	M8/M10	217 x 199 x 75	60	530
I603303050	50	M8/M10	217 x 199 x 75	60	540
I603303054	54	M8/M10	227 x 210 x 75	60	580
I603303057	56 - 57	M8/M10	227 x 210 x 75	60	600
I603303060	60.30	M8/M10	227 x 210 x 75	60	620
I603303064	64	M8/M10	239 x 221 x 75	60	640
I603303070	70	M8/M10	239 x 221 x 75	60	680
I603303076	76.10	M8/M10	249 x 232 x 75	60	720
I603303089	88.90	M8/M10	260 x 243 x 75	60	730
I603303102	101.60	M8/M10	271 x 253 x 75	60	760