


Walraven BISOFIX® PIR60 + HD500

(D0394)

for insulated pipes



Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with HD500 clamp
- HD500 clamp with M8/M10 and M10/M12 connection nut
- fire class B2
- PIR density for $D < 110\text{mm}$ = 80kg/m^3
- PIR density for $D \geq 110\text{mm}$ = 120kg/m^3
- thermal conductivity λ (approx. value): 0.30 W/(mK)
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range $-45\text{ }^\circ\text{C}$ - $+105\text{ }^\circ\text{C}$

Product Number	Outside Pipe Diameter	Connection Thread	Total Width x Total Height x Insulation Thickness Total Length		Maximum Allowed Load $F_{a,z}$
Reference letter	D	G	W x H x L	Is	$F_{a,z}$
Unit description	(mm)		(mm) x (mm) x (mm)	(mm)	(N)
I603306108	108	M16	299 x 263 x 75	60	800
I603306114	114.30	M16	322 x 277 x 75	60	1790
I603306133	133	M16	335 x 290 x 100	60	2190
I603306140	139.70	M16	345 x 300 x 100	60	2280
I603306159	159	M16	360 x 315 x 100	60	2450
I603306168	168.30	M16	367 x 324 x 100	60	2620