


## Walraven BISOFIX® PIR80 + HD500

(D0398)

for insulated pipes



### Features & benefits

- for combination with rigid foam insulation
- cover joints with aluminium tape
- insulating pipe support with HD500 clamp
- HD500 clamp with M8/M10 and M10/M12 connection nut
- does not contain CFC, HCFC, formaldehyde or cadmium
- fire class B2
- PIR density for  $D < 110\text{mm}$  =  $80\text{kg/m}^3$
- PIR density for  $D \geq 110\text{mm}$  =  $120\text{kg/m}^3$
- product is part of the Walraven Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- stands min. 1,000 hours salt spray test (max. 5% red rust) according to ISO 9227
- temperature range  $-45\text{ }^{\circ}\text{C}$  -  $+105\text{ }^{\circ}\text{C}$

Product Number	Outside Pipe Diameter	Connection Thread	Total Width x Total Height x Insulation Thickness Total Length		Maximum Allowed Load $F_{a,z}$
Reference letter	<i>D</i>	<i>G</i>	<i>W x H x L</i>	<i>I<sub>s</sub></i>	<i>F<sub>a,z</sub></i>
Unit description	(mm)		(mm) x (mm) x (mm)	(mm)	(N)
I803306089	88.90	M16	335 x 290 x 75	80	800
I803306100	100	M16	345 x 300 x 75	80	820
I803306114	114.30	M16	360 x 315 x 75	80	1860
I803306120	120	M16	367 x 324 x 75	80	2150