

Walraven Rubberfoot Support System Kit (Aluminium Rail)

(E2005)



Features & benefits

- assembled Kit ready to install to support small units like climate unit, heat pumps etc.
- kit contains 2 pieces of rubberfoot Type aluminium rail and 4 pieces of T-bolt assembly M8x40mm
- does not penetrate the waterproof membrane (at PVC roofs a separating layer must be installed to protect against plasticizer migration - see Walraven BIS Yeti® Triplex Separation Layer)
- material: vulcanized rubber, black; Rail made from aluminium
- For a detailed calculation and for support how to spread the load please contact Walraven Technical Support.
- In cases where a foot is used in roof applications, the installer is obliged to verify maximum load capacity of roof before installation
- $F_{a,z}$ = max. allowed load per 1 foot

Product Number	Total Width	Total Length	Total Height	Height	Maximum Load
<i>Reference letter</i>	<i>W</i>	<i>L</i>	<i>H</i>	<i>h</i>	
<i>Unit description</i>	<i>(mm)</i>	<i>(mm)</i>	<i>(mm)</i>	<i>(mm)</i>	<i>(N)</i>
BX67687401	135	400	95	21.30	1800
BX67687601	135	600	95	21.30	2740
BX67687001	135	1000	95	21.30	4540