
Walraven RapidStrut® Base Plate G2 (BUP1000)

(H1203)

base foot to connect fixing rails





Features & benefits

- flexible base plate for Walraven RapidStrut® rails
- suitable for all Walraven RapidStrut® rail up to 82mm height
- open side of rails 41x41 can be turned to all sides
- at high loads we advise to install with throughbolts
- timesaving with pre-assembled fasteners
- material: metal parts made of steel 1.0332; spring(s) made of POM (polyoxymethylene), green
- product is part of the Walraven Walraven UltraProtect® 1000 system
- suitable for in- and outdoor applications
- tested for fire safety according to EN 1366-1





| Product Number | For Rail Type | Total Width x Total Height x Total Length | Width | Height | Length | Heart To Heart Distance | Anchoring Slot | Fixing Hole | Material Thickness | Material Thick- ness 2 | Maximum Allowed Load Faz |
|------------------|-----------------------------------|---|-------|--------|--------|-------------------------------|-------------------|----------------|-----------------------|------------------------------|--------------------------------|
| Reference letter | | WxHxL | w | h | I | k | AS | FH | MT | MT2 | Fa,z |
| Unit description | | mm x mm x mm | mm | mm | mm | mm | mm | mm | mm | mm | N |
| 665885400 | 41x21, 41x41, 41x51, 41x62, 41x82 | 85 x 180 x 107 | 50 | 73 | 100 | 130.5 | 20x14 | 13.8 | 4 | 4 | 3,636 |